



Type of fluid
AIR-WATER

Pressure
20 bar

Material
**- PAINTED STEEL
- ABS**

WITH SPRING



FIXED*



SWIVELLING



- with hose, see page 139
- without hose, max. 100 °C



In accordance with directive



* can be rendered swivelling by using the special bracket, see page 81.

DRUM COLOURS



Hoses	Connections	Seals	Swivel joint	Central pin
black rubber	galvanized steel	Viton®	brass	galvanized steel

Overall dimensions FIXED (mm)		Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
	290	186	140	196	226	98	330	300	339	135		470 x 260 x 490	
	330	186	140	196	226	98	390	350	365	155		510 x 260 x 520	
	390	186	140	196	226	98	410	390	410	155		580 x 280 x 590	
	430	186	140	197	226	97	450	415	456	264		580 x 280 x 590	
	430 ABS	186	140	197	226	110	450	425	461	259		580 x 280 x 590	
	530	203	153	221	258	104	535	510	558	315		650 x 290 x 700	
	540	300	218	227	268	165	535	510	572	315		660 x 390 x 690	
	560	488	399	238	272	348	535	510	578	315		670 x 610 x 760	

Overall dimensions SWIVELLING (mm)		Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H	
	390	184	146	106	144	98	410	390	482	155		580 x 280 x 590	
	430	208	162	118	164	97	450	415	540	264		580 x 280 x 590	
	530	228	182	154	200	104	535	510	642	315		650 x 290 x 700	
	540	300	218	227	268	165	535	510	700	315		660 x 390 x 690	

(W: width - D: depth - H: height)



	P/N		Hose supplied	Connection		Weight	
	fixed	swivelling		inlet	outlet	fixed	swivelling
s. 290	8290.100	-	without hose *	G 3/8" (f)	G 3/8" (f)	10,0 kg	-
	8290.101	-	10 m - 3/8" (995.210)	G 3/8" (f)	G 3/8" (m)	12,0 kg	-
	8290.104	-	15 m - 1/4" (993.215)	G 3/8" (f)	G 1/4" (m)	12,0 kg	-
* Hose reel capacity		inner hose ø	1/4" 5/16" 3/8"				
		max. length	16 m 14 m 10 m				
s. 330	8330.100	-	without hose *	G 3/8" (f)	G 3/8" (f)	11,2 kg	-
	8330.101	-	12 m - 3/8" (995.211)	G 3/8" (f)	G 3/8" (m)	13,5 kg	-
	* Hose reel capacity		inner hose ø	1/4" 5/16" 3/8" 1/2"			
		max. length	18 m 16 m 14 m 12 m				
s. 390	8390.100	8380.100	without hose *	G 3/8" (f)	G 3/8" (f)	13,0 kg	13,5 kg
	8390.102	8380.102	18 m - 3/8" (995.217)	G 3/8" (f)	G 3/8" (m)	16,0 kg	16,5 kg
	* Hose reel capacity		inner hose ø	1/4" 5/16" 3/8" 1/2"			
		max. length	20 m 20 m 18 m 15 m				
s. 430	8430.100	8420.100	without hose *	G 1/2" (f)	G 1/2" (f)	16,0 kg	16,5 kg
	8430.101	8420.101	12 m - 3/8" (995.212)	G 1/2" (f)	G 3/8" (m)	18,7 kg	19,2 kg
	8430.102	8420.102	18 m - 3/8" (995.218)	G 1/2" (f)	G 3/8" (m)	19,5 kg	20,0 kg
	8430.103	8420.103	10 m - 1/2" (996.210)	G 1/2" (f)	G 1/2" (m)	19,2 kg	19,7 kg
	8430.104	8420.104	15 m - 1/2" (996.215)	G 1/2" (f)	G 1/2" (m)	20,2 kg	20,7 kg
	8430.150	-	without hose **	G 1" (f)	G 3/4" (f)	17,0 kg	-
Hose reel capacity		inner hose ø	* 5/16" 3/8" 1/2" ** 5/8" 3/4"				
		max. length	20 m 20 m 16 m 14 m 8 m				
s. 430 ABS	9430.100	-	without hose *	G 1/2" (f)	G 1/2" (f)	12,5 kg	-
	9430.101	-	12 m - 3/8" (995.212)	G 1/2" (f)	G 3/8" (m)	15,2 kg	-
	9430.102	-	18 m - 3/8" (995.218)	G 1/2" (f)	G 3/8" (m)	16,0 kg	-
	9430.103	-	10 m - 1/2" (996.210)	G 1/2" (f)	G 1/2" (m)	15,7 kg	-
	9430.104	-	15 m - 1/2" (996.215)	G 1/2" (f)	G 1/2" (m)	16,7 kg	-
* Hose reel capacity		inner hose ø	5/16" 3/8" 1/2" 5/8"				
		max. length	20 m 20 m 15 m 14 m				
s. 530	8530.100	8520.100	without hose *	G 1/2" (f)	G 1/2" (f)	21,0 kg	22,0 kg
	8530.101	8520.101	20 m - 1/2" (996.220)	G 1/2" (f)	G 1/2" (m)	26,5 kg	27,5 kg
	8530.102	8520.102	25 m - 1/2" (996.225)	G 1/2" (f)	G 1/2" (m)	27,3 kg	28,3 kg
	8530.150	-	without hose **	G 1" (f)	G 1" (f)	22,0 kg	-
Hose reel capacity		inner hose ø	* 3/8" 1/2" 5/8" ** 3/4" 1"				
		max. length	25 m 25 m 22 m 12 m 8 m				
s. 540	8540.100	8550.100	without hose *	G 1" (f)	G 1" (f)	28,0 kg	33,5 kg
	8540.101	8550.101	15 m - 3/4" (997.215)	G 1" (f)	G 3/4" (m)	35,0 kg	40,5 kg
	8540.102	8550.102	20 m - 3/4" (997.220)	G 1" (f)	G 3/4" (m)	36,5 kg	42,0 kg
	8540.103	8550.103	15 m - 1" (998.215)	G 1" (f)	G 1" (m)	38,6 kg	44,1 kg
	8540.105	8550.105	without hose **	G 1/2" (f)	G 1/2" (f)	28,5 kg	34,0 kg
	8540.106	8550.106	30 m - 1/2" (996.230)	G 1/2" (f)	G 1/2" (m)	36,4 kg	41,9 kg
Hose reel capacity		inner hose ø	* 5/8" 3/4" 1" ** 3/8" 1/2" 5/8"				
		max. length	20 m 20 m 15 m 30 m 30 m 30 m				
s. 560	8560.100	-	without hose *	G 1" (f)	G 1" (f)	48,0 kg	-
	8560.101	-	30 m - 3/4" (997.230)	G 1" (f)	G 3/4" (m)	60,0 kg	-
	8560.103	-	40 m - 3/4" (997.240)	G 1" (f)	G 3/4" (m)	63,0 kg	-
	8560.104	-	20 m - 1" (998.220)	G 1" (f)	G 1" (m)	60,6 kg	-
	8560.105	-	30 m - 1" (998.230)	G 1" (f)	G 1" (m)	64,0 kg	-
	8560.106	-	without hose **	G 1/2" (f)	G 1/2" (f)	47,5 kg	-
Hose reel capacity		inner hose ø	* 5/8" 3/4" 1" ** 3/8" 1/2" 5/8"				
		max. length	50 m 40 m 30 m 60 m 60 m 60 m				



P/N	Hose supplied	Connection		Weight
		inlet	outlet	

s. 250 ABS	HOSE REEL FOR SERVICE COLUMNS WITH STEEL BRACKET AND ABS DRUM				
	92438.101	12 m - 8 x 12 mm (971.112)	G 3/8" (m)	G 1/4" (m)	7,6 kg
	92438.102	10 m - 10 x 14,5 mm (972.110)	G 3/8" (m)	G 3/8" (m)	7,8 kg

Hose guide available as accessory, see page 83

s. 290	8288.100	without hose *	G 3/8" (m)	G 3/8" (f)	9,5 kg
	8288.102	13 m - 10 x 14,5 mm (972.113)	G 3/8" (m)	G 3/8" (m)	11,3 kg
	8288.103	15 m - 8 x 12 mm (971.115)	G 3/8" (m)	G 1/4" (m)	11,0 kg
	8288.104	10 m - 6 x 10 mm (971.010)	G 3/8" (m)	G 1/4" (m)	10,5 kg
	8288.105	15 m - 6 x 10 mm (971.015)	G 3/8" (m)	G 1/4" (m)	10,9 kg

* Hose reel capacity	inner hose Ø	8 x 12	10 x 14,5
	max. length	16 m	14 m

s. 330	8328.100	without hose *	G 3/8" (m)	G 3/8" (f)	10,1 kg
	8328.102	15 m - 10 x 14,5 mm (972.115)	G 3/8" (m)	G 3/8" (m)	12,1 kg
	8328.103	18 m - 8 x 12 mm (971.118)	G 3/8" (m)	G 1/4" (m)	11,8 kg
	8328.104	8 m - 13 x 19 mm (976.108)	G 1/2" (m)	G 1/2" (m)	12,0 kg
	8328.105	12 m - 13 x 19 mm (976.112)	G 1/2" (m)	G 1/2" (m)	15,9 kg

* Hose reel capacity	inner hose Ø	8 x 12	10 x 14,5	13 x 19
	max. length	18 m	16 m	12 m

s. 390	8378.100	without hose *	G 3/8" (m)	G 3/8" (f)	13,5 kg
	8378.102	20 m - 10 x 14,5 mm (972.120)	G 3/8" (m)	G 3/8" (m)	18,2 kg
	8378.103	20 m - 8 x 12 mm (971.120)	G 3/8" (m)	G 1/4" (m)	15,4 kg
	8378.104	10 m - 13 x 19 mm (976.110)	G 1/2" (m)	G 1/2" (m)	16,6 kg
	8378.105	15 m - 13 x 19 mm (976.114)	G 1/2" (m)	G 1/2" (m)	17,0 kg

* Hose reel capacity	inner hose Ø	8 x 12	10 x 14,5	13 x 19
	max. length	18 m	16 m	12 m

s. 430	8430.100	without hose *	G 1/2" (f)	G 1/2" (f)	15,2 kg
	8438.101	10 m - 13 x 19 mm (976.111)	G 1/2" (f)	G 1/2" (m)	18,3 kg
	8438.102	15 m - 13 x 19 mm (976.115)	G 1/2" (f)	G 1/2" (m)	18,9 kg

* Hose reel capacity	inner hose Ø	10 x 14,5	13 x 19	16 x 27
	max. length	20 m	16 m	14 m