



Type of fluid
GREASE

Pressure
400-600 bar

Material
- PAINTED STEEL
- ABS

WITH SPRING



FIXED*



SWIVELLING



- with hose, see page 139
- without hose, max. 80 °C



In accordance with directive



for ABS versions

* can be rendered swivelling by using the special bracket, see page 81.

DRUM COLOURS



Hoses	Connections	Seals	Swivel joint	Central pin
black rubber	galvanized steel	polyurethane	galvanized steel	galvanized steel

Overall dimensions FIXED (mm)

Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H
330	186	140	196	226	98	390	350	365	155	510 x 260 x 520 580 x 280 x 590 580 x 280 x 590 580 x 280 x 590 650 x 290 x 700 660 x 390 x 690
390	186	140	196	226	98	410	390	410	155	
430	186	140	197	226	97	450	415	456	264	
430 ABS	186	140	197	226	110	450	425	461	259	
530	203	153	221	258	104	535	510	558	315	
540	300	218	227	268	165	535	510	572	315	

Overall dimensions SWIVELLING (mm)

Series	A	B	C	D	E	F	G	H	I	Packaging (mm) W x D x H
390	184	146	106	144	98	410	390	482	155	580 x 280 x 590 580 x 280 x 590 650 x 290 x 700 660 x 390 x 690
430	208	162	118	164	97	450	415	540	264	
530	228	182	154	200	104	535	510	642	315	
540	300	218	227	268	165	535	510	700	315	

(W: width - D: depth - H: height)



	P/N		Hose supplied	Connection		Weight	
	fixed	swivelling		inlet	outlet	fixed	swivelling
s. 330 600 bar	8330.500	-	without hose *	G 3/8" (f)	G 3/8" (f)	11,2 kg	-
s. 330 400 bar	8330.501	-	12 m - 1/4" (993.511)	G 3/8" (f)	G 1/4" (m)	15,2 kg	-

* Hose reel capacity

inner hose ø	1/4"	5/16"	3/8"	1/2"
max. length	12 m	12 m	12 m	8 m



s. 390 600 bar	8390.500	8380.500	without hose *	G 3/8" (f)	G 3/8" (f)	13,0 kg	13,5 kg
s. 390 400 bar	8390.501	8380.501	12 m - 1/4" (993.511)	G 3/8" (f)	G 1/4" (m)	17,0 kg	17,5 kg
	8390.502	8380.502	16 m - 1/4" (993.516)	G 3/8" (f)	G 1/4" (m)	18,0 kg	18,5 kg

* Hose reel capacity

inner hose ø	1/4"	5/16"	3/8"	1/2"
max. length	16 m	16 m	17 m	12 m



s. 430 600 bar	8430.500	8420.500	without hose *	G 3/8" (f)	G 1/2" (f)	16,0 kg	16,5 kg
s. 430 400 bar	8430.501	8420.501	12 m - 1/4" (993.512)	G 3/8" (f)	G 1/4" (m)	20,0 kg	20,5 kg
	8430.502	8420.502	18 m - 1/4" (993.518)	G 3/8" (f)	G 1/4" (m)	21,7 kg	22,2 kg
	8430.505	8420.505	10 m - 3/8" (995.710)	G 3/8" (f)	G 1/4" (m)	20,8 kg	21,3 kg
	8430.506	8420.506	15 m - 3/8" (995.715)	G 3/8" (f)	G 1/4" (m)	22,7 kg	23,2 kg

* Hose reel capacity

inner hose ø	5/16"	3/8"
max. length	12 m	15 m



s. 430 600 bar ABS	9430.500	-	without hose *	G 3/8" (f)	G 1/2" (f)	12,5 kg	-
s. 430 400 bar ABS	9430.501	-	12 m - 1/4" (993.512)	G 3/8" (f)	G 1/4" (m)	16,5 kg	-
	9430.502	-	18 m - 1/4" (993.518)	G 3/8" (f)	G 1/4" (m)	18,2 kg	-
	9430.505	-	10 m - 3/8" (995.710)	G 3/8" (f)	G 1/4" (m)	17,3 kg	-
	9430.506	-	15 m - 3/8" (995.715)	G 3/8" (f)	G 1/4" (m)	19,2 kg	-

* Hose reel capacity

inner hose ø	5/16"	3/8"
max. length	12 m	15 m



s. 530 600 bar	8530.500	8520.500	without hose *	G 3/8" (f)	G 1/2" (f)	21,0 kg	22,0 kg
s. 530 400 bar	8530.501	8520.501	20 m - 3/8" (995.720)	G 3/8" (f)	G 1/4" (m)	29,6 kg	30,6 kg
	8530.502	8520.502	25 m - 3/8" (995.725)	G 3/8" (f)	G 1/4" (m)	31,6 kg	32,6 kg

* Hose reel capacity

inner hose ø	3/8"	1/2"
max. length	25 m	25 m



s. 540 600 bar	8540.500	8550.500	without hose *	G 3/8" (f)	G 1/2" (f)	28,0 kg	33,5 kg
s. 540 400 bar	8540.501	8550.501	30 m - 3/8" (995.730)	G 3/8" (f)	G 1/4" (m)	41,0 kg	46,5 kg

* Hose reel capacity

inner hose ø	3/8"	1/2"	5/8"
max. length	30 m	30 m	30 m